

1D Handheld Barcode Scanner XL-626



- ⊙ Robust and classical design.
- ⊙ Easy configure and software update.
- ⊙ Support 20 countries keyboard languages.
- ⊙ With IP 54 waterproof and dustproof protection .
- ⊙ 32 bits CPU, strong decode ability on difficult codes.
- ⊙ 160~850mm(0.9mm) scan distance on big barcodes.



Model Number	XL-626	Indicator	Buzzer, Indicator
CPU	32 Bit ARM	Dimension	L x W x H: 175mm x 73mm x 102mm
Light Source	Visible Laser Diode 650nm	Weight	238g
Scan pattern	Single Scan	Material	ABS + PC
Scan Rate	100 times/second	Operating Current	90mA
Scan Precision	3mil	Voltage	DC 5V
Scan Width	30mm@scan window, 220mm@200mm	Static Current	40mA
Scan Depth of Field	20-450mm (0.33mm pcs0.9)	Laser Class	Class 1
Scan Angle	30° & 65° & 55°	EMC	CE & FCC DOC compliance
Interface	RS 232 & PS2 & USB(not interchangeable)	Operate Temperature	0°C to 45°C
Print Contrast	10% UPC/EAN 100%	Storage Temperature	- 20°C to 60°C
Decoding Capability	Industool 2 of 5, Standard 25/Matrix 25/China post 25/Code 11/Codabar/MSI/plessey/UK/plessey/Code39 (Standard 39 & Full ASCII Code 39)/Code 32/Code 93/ Code128/UPCA,UPCE,EAN13,EAN8,UPC/EAN add-on 2/5, ISBN,ISSN, GS1(RSS) RSS-14,LIMITED, EXPENDED, Include GS1 STACK		



SUNLUX IOT Technology (Guangdong) Inc.

Office Add: 4F,No.7 ,Kehui First Street ,Science Road,Science City,Guangzhou,China

Tel: +86-20-32053765 Fax: +86-20-82115390 Site: www.xl-scan.com E-mail: sales@xl-scan.com